

emcosafe



751041

SLIM LED EXIT SIGN

M3 OR NM3, IP20, Class II

UNIVERSAL LEGEND KIT

AUTOMATIC OR MANUAL TESTING

Specification:

Dimensions:	330mm wide x 185mm high x 33mm deep
Cable entries:	Rear BESA fixings and keyholes, 20mm KO: 1 to top, 1 to each side.
Legend Options:	Polycarbonate panel with universal two-part legend facia. Arrow can be rotated to suit, running man can be reversed to suit.
Emergency Power:	1W
Threshold Illuminator:	38 Lumens using separate downward facing LEDs
Emergency Duration:	3 Hours
Battery:	LiFePO4 3.2V 1.8Ah
Indicator Brightness:	Press and hold test button, after 3 seconds the green indicator will cycle through the selectable brightness levels. Release at selected level and this is automatically stored.
Test Modes:	Supplied set to auto-test, manual only testing is selectable
Commissioning:	Conducts a short function test 5 minutes after the mains supply is connected. Conducts a full duration test at a random* time between 24 and 48 hours after the mains is connected.
Testing:	Weekly 5 second Test. Annual at random* between 26 and 52 weeks.

** randomisation is to reduce the likelihood of two or more signs being depleted at any one time.*

Bi-Colour LED Status:	Green On	Normal healthy status
	Green Slow Flash (0.5s)	Duration Test pending
	Green Med Flash (0.25s)	Annual Test Duration test running
	Green Fast Flash (0.15s)	Functional test running
	Red On	Battery/Charging failure
	Red Fast Flash	Lightsource failure
	Red Slow Flash	Battery duration failure

ORDER CODES: **751041** Slim LED Exit Sign c/w Legend Panel

T: 01992 582033

E: sales@emcogroup.co.uk