

emcosafe



711009

**IP65 M/NM3 Bulkhead
Manual or Automatic Testing
c/w exit legend kit**

Specification:

Dimensions:	355mm x 115mm x 63mm, quick release hinged gear tray
Entries:	Rear BESA drill starts, 20mm KO to each end, and one for side entry
Input Power:	3.5W Max @ 220/240V
Emergency Power:	1W
Colour Temperature:	6000-6500K
Maintained Mode:	210 Lumens
Emergency Mode:	150 Lumens
Emergency Duration:	3 Hours
Battery:	LiFePO4 3.2V 1.5Ah

Selectable Test Modes: Manual Testing selectable by dip-switch on printed circuit board or
Automatic Self-Testing conforming with IEC 62034

Automatic Test Regime: First function test 24 hours after connection to the electrical supply
Functional test at monthly intervals
Full duration test (3 hours) at 6 monthly intervals

Bi-Colour LED Status:

Green On	Normal healthy status
Green Fast Flash	Functional test running
Green Slow Flash	Duration test running
Red On	Battery failure
Red Fast Flash	Duration failure—insufficient battery capacity
Red Slow Flash	Lightsource failure

T: 01992 582033

E: sales@emcogroup.co.uk

emcosafe



711009

**IP65 M/NM3 Bulkhead
Manual or Automatic Testing
c/w exit legend kit**

Ancillary Items for 711009:



The 711009 bulkhead is supplied with a self-adhesive legend kit which the installer can apply to the diffuser.

This item is included in the 711009 carton with the product.

711009/EXTKIT

Polycarbonate drop-down diffuser. Maintains the IP65 rating so is suitable for interior use as well as in car parks, subways, plant rooms, and other exterior or damp locations.

Supplied with 2 x self-adhesive legend kits for double-sided exit sign use.

The depth of the diffuser is 185mm. The depth of the base is 32mm giving a total product height of 217mm when fitted.

The viewing distance is 30 metres.

711009/RECKIT

Bezel kit for semi-recessing the 711009 bulkhead.

The trim is manufactured from polycarbonate with four steel butterfly springs for ease of fixing.

The recommended cut-out size is : 360mm x 126mm.